

LIS007283962B2

(12) United States Patent

Meyerhoff et al.

(10) Patent No.: US 7,283,962 B2

(45) **Date of Patent:**

Oct. 16, 2007

(54)	METHODS AND SYSTEMS FOR
	DETECTING, MEASURING, AND
	MONITORING STRESS IN SPEECH

(75) Inventors: James L. Meyerhoff, Silver Spring,

MD (US); John H. L. Hansen,

Louisville, CO (US)

(73) Assignee: United States of America as

Represented by the Secretary of the

Army, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 860 days.

(21) Appl. No.: 10/392,881

(22) Filed: Mar. 21, 2003

(65) **Prior Publication Data**

US 2007/0213981 A1 Sep. 13, 2007

Related U.S. Application Data

- (60) Provisional application No. 60/368,806, filed on Mar. 21, 2002.
- (51) **Int. Cl. G10L 21/00**

(2006.01)

(52) **U.S. Cl.** **704/270**; 704/275; 704/251

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,367,454 A * 11/1994 Kawamoto et al. 715/706

5,539,860	A 26	7/1006	DeSimon a et al. 704/224
3,339,800	A	//1990	DeSimone et al 704/234
5,647,834	A *	7/1997	Ron 600/23
5,987,415	A *	11/1999	Breese et al 704/270
6,006,188	A *	12/1999	Bogdashevsky et al 704/270
6,151,571	A *	11/2000	Pertrushin 704/209
6,173,260	B1*	1/2001	Slaney 704/250
6,463,415	B2*	10/2002	St. John 704/273
2003/0033145	A1*	2/2003	Petrushin 704/236
2003/0078768	A1*	4/2003	Silverman et al 704/206

* cited by examiner

Primary Examiner—Vijay Chawan (74) Attorney, Agent, or Firm—Elizabeth Arwine

(57) **ABSTRACT**

As disclosed herein, the present invention provides methods and systems for detecting, measuring, or monitoring the presence of absence of at least one emotion in a subject from a speech sample obtained from the subject. In particular, the methods and systems of the present invention comprise extracting at least one feature from the speech sample, assigning the speech sample a score using a weighted frequency band scoring scheme, and comparing the score with a general reference model or a control. As disclosed, the methods, systems and computer programs of the present invention provide detection error rates of about 4.7% or less, preferably about 3.0% or less, more preferably about 2.0% or less, most preferably about 1.0% or less and thereby reduced the detection error rate by about 60.0% or more, preferably about 70.0% or more, more preferably about 80.0% or more, even more preferably about 90% or more, and most preferably 95.0% or more than the detection error rates of prior art methods.

39 Claims, 4 Drawing Sheets

